GE APPLIANCES

CONNECT SERIES

VARIABLE SPEED HEAT PUMP SYSTEMS

SPECIFICATIONS

	COOLING AND HEATING CAPACITY	24,000 BTU	36,000 BTU	48,000 BTU	60,000 BTU
COOLING	SEER	20	18	18	17
	EER	12.5	10	11.5	10.5
HEATING	HSPF	10.5	10	10.5	10
	Electric Backup Heat Kits	5kW/8kW/10kW		10kW/15kW/20kW	
OUTDOOR UNIT	MCA	24		35	
	MOP	35		45	
	Breaker Size A	35		40	
	Outdoor Noise Level - dB	57		58	
	Dimension: H x W x D - in. (mm)	32 1/4 x 37 x 18 1/8 (820 x 940 x 460)		53 3/4 x 42 3/4 x 14 5/8 (1365 x 1085 x 370)	
	Weight Net/Gross - lbs. (kg)	217.2/240.3 (98.5/109)		308.6/337.3 (140/153)	
INDOOR UNIT	Airflow CFM	960	1000	1380	1600
	Indoor Sound Level - dB	47	47	51	51
	Metering Device	TXV	TXV	TXV	TXV
	Breaker Size A	15		15	
	Maximum Static Pressure W.C.	1.0		1.0	
	Dimension: H x W x D - in. (mm)	48 1/4 x 21 1/4 x 211/4 (1226 x 540 x 540)		57 x 24 3/4 x 211/4 (1448 x 630 x 540)	
	Weight Net/Gross - lbs. (kg)	156.5/169.8 (71/77)		202.8/218.3 (92/99)	
CONTROL	Control Voltage	24VAC		24VAC	
PIPING	Refrigerant Type	R410A		R410A	
	Liquid O.D. - in.	3/8		3/8	
	Suction O.D. - in.	3/4		3/4	
	Piping Connection	BRAZE		BRAZE	
	Factory Charge - lbs. (kg)	9.81 (4.45)		14.33 (6.5)	
	Maximum Line Length - ft. (m)	164 (50)		98 (30)	
	Maximum Height - ft. (m)	50 (15)		50 (15)	

CONNECT WITH GE APPLIANCES

To learn more about Connect Series Heat Pump Systems, go to **https://www.geappliances.com/ductless** or contact your dealer.

GE APPLIANCES

Pub No: 26-0006
Rev: 12-02-21